CHEMSOL

Your Chemical Solutions Provider

TECHNICAL DATA SHEET
MIL-DTL-24607B
NON-FLAMING (INTUMESCENT) ENAMEL

PRODUCT: A government specification, non-flaming enamel formulated to meet MIL-DTL-24607B.

DESCRIPTION: MIL-DTL-24607B NON-FLAMING ENAMEL is an intumescent, non-flaming coating that is resistant to burning and flaming.

PROPERTIES:

COLORS..... Per Fed-Std 595C
FINISH..... Semigloss
SOLIDS(Weight)..... 79- 82%
PIGMENT(Weight)..... 52 - 54%
VISCOSITY..... 80 - 90 KU
DRYING TIMES:
TO TOUCH..... 2 Hours
DRY HARD..... 5 hours

ADVANTAGES:

(1). Non-Flaming (intumescent) Properties
(2). Meets MIL-DTL-24607B
(3). Resistant to Burning
(4). Air Dry Semi-gloss Finish

USES:

(1). Aerospace Applications
(2). Submarines
(3). Factories
(4). Industrial Facilities

APPLICATION: Apply by brush, roller or spray methods. For brush and roll, thin with Mineral Spirits Reduce at 10% by volume. For spray application, thin with Xylene at 10-15% by volume. Apply to a dry film thickness of 1.5 - 2.0 mils.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.
USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
CONTENTS ARE FLAMMABLE.

8423 Boettner Road • Bridgewater, MI 48115 • (888)697-6001 • Fax (734)944-3781
Website http://www.chemsol.com